

Package: ROI.plugin.qpoases (via r-universe)

September 16, 2026

Version 1.0-4

Title 'qpOASES' Plugin for the 'R' Optimization Infrastructure

Description Enhances the 'R' Optimization Infrastructure ('ROI') package with the quadratic solver 'qpOASES'. More information about 'qpOASES' can be found at <https://github.com/coin-or/qpOASES>.

Imports methods, slam, ROI (>= 1.0-0), Rcpp (>= 0.12.11), checkmate

License GPL-3

LinkingTo Rcpp

URL <https://roigrp.gitlab.io>,
<https://gitlab.com/roigrp/solver/ROI.plugin.qpoases>

Config/roxygen2/version 8.0.0

Repository <https://roigrp.r-universe.dev>

Date/Publication 2026-08-16 16:23:15 UTC

RemoteUrl <https://gitlab.com/roigrp/solver/roi.plugin.qpoases>

RemoteRef HEAD

RemoteSha 873df423adc00a9d3d5c8294ada0eed0f4e29bc7

Contents

ROI.plugin.qpoases-package	2
Example-1	2

Index	4
--------------	----------

ROI.plugin.qpoases-package
qpOASES

Description

This package provides an interface to qpOASES. pOASES is an open-source C++ implementation of the online active set strategy, which was inspired by important observations from the field of parametric quadratic programming (QP).

References

H.J. Ferreau and C. Kirches and A. Potschka and H.G. Bock and M. Diehl. qpOASES: A parametric active-set algorithm for quadratic programming, “Mathematical Programming Computation”, 2014
 H.J. Ferreau and H.G. Bock and M. Diehl. An online active set strategy to overcome the limitations of explicit MPC, “International Journal of Robust and Nonlinear Control”, 2008
 H.J. Ferreau and A. Potschka and C. Kirches. qpOASES “webpage” <https://github.com/coin-or/qpOASES>, 2017

Example-1

Quadratic Problem 1

Description

$$\begin{aligned}
 &\text{maximize } x_1^2 + x_2^2 + x_3^2 - 5x_2 \\
 &\text{subject to :} \\
 &-4x_1 - 3x_2 + \geq -8 \\
 &2x_1 + x_2 + \geq 2 \\
 &-2x_2 + x_3 \geq 0 \\
 &x_1, x_2, x_3 \geq 0
 \end{aligned}$$

Examples

```

Sys.setenv(ROI_LOAD_PLUGINS = "FALSE")
library("ROI")
library("ROI.plugin.qpoases")

A <- cbind(c(-4, -3, 0),
           c( 2,  1, 0),
           c( 0, -2, 1))
x <- OP(Q_objective(diag(3), L = c(0, -5, 0)),
        L_constraint(L = t(A),

```

```
dir = rep(">=", 3),  
rhs = c(-8, 2, 0))  
  
opt <- ROI_solve(x, solver="qpoases")  
opt  
## Optimal solution found.  
## The objective value is: -2.380952e+00  
solution(opt)  
## [1] 0.4761905 1.0476190 2.0952381
```

Index

Example-1, [2](#)

ROI.plugin.qpoases-package, [2](#)